

## 40-0912.pdf

**Model #:** 40-0912  
**UPC:** #049448091201  
**MSRP:** \$146.12



Self-leveling within +/-6 degrees, Interior horizontal and vertical layout, Locking mechanism protects inner pendulum during transportation, 360 degrees graduated base allows angle layout, Emits cross line lasers, Projects vertical and horizontal laser lines simultaneously, Visual out of level indicator, 5/8" - 11 thread, 40-0912 Includes > Laser, 3 "AAA" alkaline batteries, instruction manual with warranty card, soft-sided carrying case

### PRODUCT DETAILS

40-0912 Includes > Laser, 3 "AAA" alkaline batteries, instruction manual with warranty card, soft-sided carrying case

- Self-leveling
- Interior horizontal and vertical layout
- Locking mechanism protects inner pendulum during transportation
- 360 degrees graduated base allows angle layout
- Emits cross line lasers
- Projects vertical and horizontal laser lines simultaneously
- Visual out of level indicator
- 5/8" - 11 thread

## SPECIFICATIONS

<b>Accuracy</b>	+/-1/4"/35' (+/-0.6mm/m)
<b>Battery Life</b>	Approximately 12 hours continuous use
<b>Center Screw Thread</b>	5/8"-11
<b>Dimensions</b>	5" x 4" x 3.5" (127x102x89mm)
<b>Interior Range</b>	Up to 100ft. (30m) depending upon light conditions
<b>IP Protection Class</b>	54
<b>Laser Classification</b>	Class IIIa
<b>Laser Wavelength</b>	635nm+/-10nm (Red)
<b>Leveling Method</b>	Self-leveling (Pendulum)
<b>Maximum Power Output</b>	Less than/Equal to 5mW
<b>Power Supply</b>	3 "AAA" alkaline batteries (included in 40-0912)
<b>Self-Leveling Range</b>	+/- 6 degrees
<b>Warranty</b>	3 Year Warranty
<b>Weight</b>	1.2lbs (0.54kg)
<b>Working Temperature</b>	14 degrees to 113 degrees (-10 degrees celsius to +45 degrees celsius)