

/files/manuals/40-6690EnglishManual.pdf|/files/manuals/40-6690SpanishManual.pdf

Model #: 40-6690
UPC: #049448066902
MSRP: \$4,100.00



Large, illuminated LCD display makes information easy to see and use, Easy grade input to enter by individual digit for quick set-up changes, Infrared remote control works over long distances providing real time data between remote and pipe laser, Laser dot center feature automatically centers laser dot on target, Battery indicator monitors battery level in rechargeable and alkaline battery packs, Sleep mode turns off laser beam and display, 40-6690 Includes > Laser, NiMH rechargeable battery pack, alkaline battery comparent (batteries not included), remote control w/9V battery, small and large target, car adapter charger w/conversion plug, 6.4V AC battery adapter, 5 leg sets, instruction manual with warranty card, hard-shell carrying case

PRODUCT DETAILS

40-6690 Includes > Laser, NiMH rechargeable battery pack, alkaline battery comparent (batteries not included), remote control w/9V battery, small and large target, car adapter charger w/conversion plug, 6.4V AC battery adapter, 5 leg sets, instruction manual with warranty card, hard-shell carrying case

- Large, illuminated LCD display makes information easy to see and use
- Easy grade input to enter by individual digit for quick set-up changes
- Infrared remote control works over long distances providing real time data between remote and pipe laser
- Laser dot center feature automatically centers laser dot on target
- Battery indicator monitors battery level in rechargeable and alkaline battery packs
- Sleep mode turns off laser beam and display

SPECIFICATIONS

Accuracy	+/-1/16"/100ft. (+/-5mm/100m; +/-10 arc sec)
Dimensions	5.19" x 14.96" (132x380mm)
Grade Display	0.00%
Grade Setting	-20% to +40%
IP Protection Class	68
Laser Classification	Class IIIa
Laser Wavelength	635nm +/-10nm (Red)
Left and Right Scan	+/- 4 degrees
Leveling Method	Automatic (Electronic)
Maximum Power Output	Less than/Equal to 5mW
Power Supply	NiMH rechargeable battery pack (included), 6.4V adapter and 12V car charger (included) or 4 "D" alkaline batteries (not included)
Remote Range	Front 300', rear 50'
Self-Leveling Range	+/- 5 degrees
Warranty	3 Year Warranty
Weight	13.2lbs (6 kg)
Working Range Angle	Up to 800' (245m)
Working Temperature	-4 degrees +122 degrees (-20degrees celcius to +50degrees celcius)

APPLICATION

The Johnson Level 40-6690 can be used for the following applications; aligning storm, sanitary or other gravity flow drainage pipes.