

/files/manuals/40-6060English.pdf|/files/manuals/40-6060French.pdf|/files/n6060Spanish.pdf

Model #: 40-6060
UPC: #049448060603
MSRP: \$191.06



5 construction languages - units of measure (degrees, percent, mm/m, in/ft in decimal, in/ft in fractional) for overhead measurements, Push button calibration, Audible indicator for level 0 degrees and plumb 90 degrees, Working range 0 x 90 degrees, Accuracy +/- 0.1 degrees at 0 degrees, 90 degrees, 40-6060 Includes > 6" Magnetic digital level, 3 "AAA" alkaline batteries, instruction manual, soft-sided pouch

PRODUCT DETAILS

40-6060 Includes: Magnetic digital level, 3 "AAA" alkaline batteries, instruction manual, soft-sided pouch

- 5 construction languages - units of measure (degrees, percent, mm/m, in/ft in decimal, in/ft in fractional)
- Automatic digit inversion for overhead measurements
- Backlight for easy-read in dimly lit work environment
- Powerful GripTight rare earth magnets hold to ferrous metal surfaces
- Push button calibration
- Audible indicator at 0 and 90 degrees

SPECIFICATIONS

Accuracy	±0.1° for 0° and 90°, and ±0.2° for 1° to 89°
Automatic Shut-off	20 minutes
Battery Life	Approximately 100 hours continuous use
Center Screw Thread	1/4"-20
Dimensions	6.45" x 2.3" x 1.25" (156 x 56 x 31mm)
Power Supply	3 "AAA" alkaline batteries (included)
Resolution	±0.1°, 0.1%, 1/8", 0.02", 1.7mm
Warranty	3 Year Warranty
Weight	0.66 lbs. (0.30kg)
Working Range	0 x 90 degrees
Working Temperature	14 degrees to 113 degrees (-10 degrees celsius to +45 degrees celsius)

APPLICATION

The Johnson Level 40-6060 can be used for following indoor and outdoor applications; machine installation for level and plumb, handicap ramp installation, measuring slope or incline.