

**/files/manuals/40-6065%20English.pdf|/files/manuals/40-6065%20French.pdf|/files/manuals/40-6065%20Spanish.pdf**

**Model #:** 40-6065  
**UPC:** #049448060658  
**MSRP:** \$325.94



5 construction languages - units of measure (degrees, percent, mm/m, in/ft in decimal, in/ft in fractional), Working range of angle measurement is 0 degrees to 182.5 degrees, Automatic digit inversion for overhead measurements, Laser beam for transfer of reference points, Push button calibration, Audible indicator at 0 degrees and 90 degrees, V-groove, Includes 40-6065 > 21" Magnetic digital level/angle locator with dot laser, 3 "AA" alkaline batteries, instruction manual, soft-sided pouch

## PRODUCT DETAILS

40-6065 Includes: Magnetic digital level/angle locator with dot laser, 3 "AA" alkaline batteries, instruction manual, soft-sided pouch

- 5 construction languages - units of measure (degrees, percent, mm/m, in/ft in decimal, in/ft in fractional)
- Working range of angle measurement is 0 degrees to 182.5 degrees
- Automatic digit inversion for overhead measurements
- Backlight for easy-read in dimly lit work environment
- Laser beam for transfer of reference points
- Powerful GripTight rare earth magnets hold to ferrous metal surfaces
- Push button calibration
- Audible indicator at 0° and 90°

## SPECIFICATIONS

<b>Accuracy</b>	+/-0.1° for 0 and 90, +/-0.2° for other angles
<b>Accuracy Angle</b>	+/-0.1 degrees
<b>Battery Life</b>	Approximately 70 hours continuous use
<b>Center Screw Thread</b>	1/4"-20
<b>Dimensions</b>	20.8" x 2.48" x 1.57" (600 x 63 x 40mm)
<b>Laser Accuracy</b>	+/-1/8"/50ft. ( $\pm$ 0.2mm/m)
<b>Laser Classification</b>	Class IIIa
<b>Laser Wavelength</b>	650nm+/-10
<b>Maximum Power Output</b>	Less than/Equal to 5mW
<b>Power Supply</b>	3 "AA" alkaline batteries and 1 3V CR 2032 lithium battery (included)
<b>Resolution</b>	0.10%
<b>Warranty</b>	3 Year Warranty
<b>Weight</b>	2.64 lbs. (1.2kg)
<b>Working Angle Inclination</b>	0-90 degrees
<b>Working Range Angle</b>	0-182.5 degrees
<b>Working Temperature</b>	14 degrees to 113 degrees (-10 degrees celsius to +45 degrees celsius)

## APPLICATION

The Johnson Level 40-6065 can be used for the following indoor and outdoor applications; machine installation for level and plumb, handicap ramp installation, measuring slope or incline, measure angles, bend pipe or sheet metal at precise angles, window and door installation, counter top installation.