

/files/manuals/40-6200%20Instruction%20Manual.pdf

Model #: 40-6200
UPC: #049448620005
MSRP: \$1,463.00



Decrease vibration on any Pulley/Sheave System - minimize belt and motor bearing wear, Compact size - easy to use on small diameter sheaves, Faster set ups, Decrease bearing wear, Green beam is 400% more visible than red beam laser, Use as a laser level - check the height and flatness of motor and gear box mounting plates, Aligns belts, pulleys, sheaves, sprockets, gear trains, rollers, platforms, conveyors, and other plant equipment Includes > Red or green magnetic sheave alignment, three precision machined magnetic targets, 2 "AAA" alkaline batteries, instruction manual, hard-shell carrying case

PRODUCT DETAILS

40-6200 Includes > Red magnetic sheave alignment, three precision machined magnetic targets, instruction manual with warranty card, hard-shell carrying case

- Decrease vibration on any Pulley/Sheave System - minimize belt and motor bearing wear
- Compact size - easy to use on small diameter sheaves
- Faster set ups
- Green beam is 400% more visible than red beam laser
- Use as a laser level - check the height and flatness of motor and gear box mounting plates
- Aligns belts, pulleys, sheaves, sprockets, gear trains, rollers, platforms, conveyors, and other plant equipment Includes > Red or green magnetic sheave alignment, three precision machined magnetic targets, 2 "AAA" alkaline batteries, instruction manual, hard-shell carrying case

SPECIFICATIONS

Accuracy	+/-1/16"/10ft. (+/-1.5mm/3m)
Battery Life	Approximately 10 hours continuous use
Beam Spread	60"/3'
Dimensions	1.75" x 6.75" x 0.625" (144x171x15mm)
Interior Range	Up to 100ft. (30m) depending upon light conditions
IP Protection Class	67
Laser Classification	Class II
Laser Wavelength	532nm (Green), 635nm+/-10nm (Red)
Line Width	+/-1//16"/30'
Magnets	Nickel Plated Rare Earth
Maximum Power Output	Less than/Equal to 1mW
Operating Distance	50'
Optics	Nickel Plated Rare Earth
Power Supply	2 "AAA" alkaline batteries (included)
Targets	3 Retro-Reflective, adjustable over 1"
Vial	40 Arc Minute
Warranty	1 Year Warranty
Weight	14 oz. (0.39 kg)

APPLICATION

The Johnson Level 40-6200 can be used for the following indoor applications; aligning belts, sheaves, sprockets, gear trains, rollers, platforms, conveyors and other plant equipment.