



CHARACTERISTICS:

- Measuring tolerance Solatronic module:
0.05° at 0° and 90°
0.1° between 1° and 89°
- Adjustable inclination display in °, % and mm/m
- "Hold" function for storing measured values and for transferring angles
- Switchable audible signal guidance in difficult visible conditions
- Comfortable reading through a reversible display for inverted measurements

APPLICATIONS:

- Horizontal measurement
- Vertical measurement
- Angle/inclination measurement

DL

| Model | Length |
|-----------------|---------|
| DL 24" - LSB24D | 24 inch |
| DL 48" - LSB48D | 48 inch |

Technical details:

| | |
|--|-------------------------------------|
| Item description | Electronic inclination spirit level |
| Dimension | 59 x 27 |
| Protection class | IP65 |
| Material | Aluminium |
| Surface | epoxy coated |
| Colour | red |
| Profile weight | 890 g/m |
| Measuring tolerance standard position | 0.30 mm/m (0.017°) |
| Measuring tolerance inverted measurement | 0.50 mm/m (0.029°) |
| Number of horizontal vials | 1 |
| Number of vertical vials | 1 |
| Special characteristic | Solatronic module |
| Measuring surface | epoxy coated |
| End caps | 1-c + 2-c |

Included accessory:

- Carrying case