

Nedo Aluminum Tripods



Nedo aluminum tripods are robust and very solid. They are suitable for the every day use with levels, builders' theodolites and rotating lasers. Thanks to the tried and proven quick-clamping system, the tripods' legs can be extended and fixed very easily.



Short Medium-Duty Tripod

Features	Suitable for
<ul style="list-style-type: none"> ▪ Strong aluminum extension legs, silver anodized ▪ Tripod head made of aluminum, powder-coated ▪ Break-proof quick release levers, made of aluminum ▪ Brass hinge pins for extra stability ▪ Tripod feet made of high-tech plastic material w/ steel points ▪ Retract-and-go transport locking system 	<ul style="list-style-type: none"> ▪ Dot and line lasers ▪ Rotating lasers
Ref.-No. 200 631	
Min. effective height	approx. 23" / 0.60 m
Max. effective height	approx. 33" / 0.80 m
Retracted length	approx. 24" / 0.60 m
Holding screw	5/8" x 11 thread
Weight	6.6 lbs. / 3.00 kg
Tripod head	flat , ø 5.5" / 140 mm

Features	Suitable for
<ul style="list-style-type: none"> ▪ Strong aluminum extension legs, silver anodized ▪ Tripod head made of aluminum, powder-coated 	<ul style="list-style-type: none"> ▪ Dot and line lasers ▪ Rotating lasers



- Break-proof quick release levers, made of aluminum
- Brass hinge pins for extra stability

Ref.-No. 200 412

Min. effective height	approx. 31" / 0.80 m
Max. effective height	approx. 47" / 1.20 m
Retracted length	approx. 32" / 0.80 m
Holding screw	5/8" x 11 thread
Weight	8.8 lbs. / 4.00 kg
Tripod head	flat , ø 5.5" / 140 mm



Medium-Duty Aluminum Tripod

Features	Suitable for
----------	--------------

- | | |
|---|---|
| <ul style="list-style-type: none"> ▪ Strong aluminum extension legs, silver anodized ▪ Tripod head made of aluminum, powder-coated ▪ Break-proof quick release levers, made of aluminum ▪ Brass hinge pins for extra stability ▪ Tripod feet made of aluminum w/ steel points ▪ Retract-and-go transport locking system | <ul style="list-style-type: none"> ▪ Builders' levels ▪ Rotating lasers |
|---|---|

Ref.-No. 200 221

Min. effective height	approx. 36" / 0.91 m
Max. effective height	approx. 66" / 1.69 m
Retracted length	approx. 42" / 1.06 m
Holding screw	5/8" x 11 thread
Weight	7.5 lbs. / 3.40 kg
Tripod head	flat , ø 5.5" / 140 mm



Heavy-Duty Aluminum Tripod

Features	Suitable for
----------	--------------

- | | |
|---|--|
| <ul style="list-style-type: none"> ▪ Strong aluminum extension legs, silver anodized ▪ Tripod head made of aluminum, powder-coated ▪ Break-proof quick release levers, made of aluminum ▪ Brass hinge pins for extra stability ▪ Tripod feet made of aluminum ▪ Carrying strap ▪ Retract-and-go transport locking system | <ul style="list-style-type: none"> ▪ Builders' levels ▪ Rotating lasers ▪ Theodolites |
|---|--|

Ref.-No. 200225

Min. effective height	approx. 40" / 1.00 m
Max. effective height	approx. 66" / 1.70 m
Retracted length	approx. 42" / 1.00 m
Holding screw	5/8" x 11 thread

Weight 8.3 lbs. / 3.8 kg
 Tripod head **flat**, \varnothing 5.5" / 140 mm



Heavy-Duty Aluminum Tripod

Features	Suitable for
<ul style="list-style-type: none"> ▪ Strong aluminum extension legs, silver anodized ▪ Tripod head made of aluminum, powder-coated ▪ Break-proof quick release levers, made of aluminum ▪ Brass hinge pins for extra stability ▪ Tripod feet made of aluminum w/ replaceable steel points ▪ In accordance with ISO 12858-2-LF 	<ul style="list-style-type: none"> ▪ Builders' levels ▪ Rotating lasers ▪ Theodolites
Ref.-No. 200 200-185	
Min. effective height	approx. 43" / 1.10 m
Max. effective height	approx. 68" / 1.70 m
Retracted length	approx. 45" / 1.10 m
Holding screw	5/8" x 11 thread
Weight	11 lbs. / 5.00 kg
Tripod head	flat , \varnothing 5.5" / 140 mm



Tripod Ref.-No. 200 204-185

Features	Suitable for
<ul style="list-style-type: none"> ▪ Aluminium tripod plate ▪ Large, round tripod head ▪ Quick clamp ▪ Snap Cap ▪ Carrying strap ▪ In accordance with ISO 12858-2-H 	<ul style="list-style-type: none"> ▪ Builders' levels ▪ Theodolites ▪ Total stations ▪ Rotating lasers
Tripod Ref.-No. 200204-185	
Min. effective height	approx. 1.02 m
Max. effective height	approx. 1.72 m
Retracted length	approx. 1.10 m
Weight	approx. 5.20 kg
Holding screw	5/8" thread
Tripod head	flat , \varnothing 167 mm

Features	Suitable for
<ul style="list-style-type: none"> ▪ Strong aluminum extension legs, silver anodized ▪ Large round tripod head made of aluminum, powder-coated 	<ul style="list-style-type: none"> ▪ Builders' levels ▪ Theodolites ▪ Total stations ▪ Rotating lasers



- Snap Cap
- Break-proof quick release levers, made of aluminum
- Brass hinge pins for extra stability
- Tripod feet made of aluminum w/ replaceable steel point
- Carrying strap
- In accordance with ISO 10370-2:11

Ref.-No. 200 524-185

Min. effective height	approx. 41" / 1.10 m
Max. effective height	approx. 67" / 1.70 m
Retracted length	approx. 45" / 1.10 m
Holding screw	5/8" x 11 thread
Weight	14 lbs. / 6.40 kg
Tripod head	flat , ø 6.5" / 167 mm
