# LD-12 WATER LEAK DETECTOR



#### **FEATURES**

- ▶ Large meter display (with backlight) of sound loudness, allowing the user to pinpoint the exact leak location.
- ▶ Light weight amplifier, weighing only 31 ounces, with a padded carrying case and a strap.
- Six selectable filters, split into three "low side" filters (100Hz, 200Hz, or 400Hz) and three "high side" filters (600Hz, 800Hz, or 1200Hz).
- "Limiter" switch which cuts off all loud noises greater than 110dB. If you drop the sensor, you won't hurt your hearing.
- ► "Filter-Thru" switch, which turns OFF all of the amp's filters, allowing the user to hear all sounds from 50Hz to 15,000Hz.
- High-sensitivity ground microphone and low "electronic noise" amplifier combine to offer the very best quality sound for leak detection.
- > Three accessories for attachment to the sensor:
  - ▶ Ground plate for pinpointing on streets/slabs
  - ▶ Magnet base for surveying at hydrants/valves
  - ▶ Contact rod for surveying at meters/fittings



AMPLIFIER WITH METER DISPLAY AND FILTER CONTROLS

#### **AMPLIFIER CONTROLS**

- ▶ Power ON/OFF Switch
- Battery Indicator
- ▶ Adjustable Filter buttons
- ▶ Headphone Jack
- ⊳ Sensor Jack
- Meter Display

## **SPECIFICATIONS**

### **AMPLIFIER**

▶ Input Impedance: 50k ohms

Output Impedance: 15 ohms

→ Amplification: 62 dB +/- 3dB

▶ Frequency Range:

1) 100Hz to 1200Hz (13 dB) with Filter-Thru OFF 2) 15Hz to 30,000Hz (13 dB) with Filter-Thru ON

- > Power: 6 AA dry cell batteries
- ▶ Power Consumption:
  - 1) 70 mA or less with backlight ON
  - 2) 35 mA or less with backlight OFF
- ▶ Battery Life:
  - 1) 28 hours with backlight OFF (alkaline cells)
  - 2) 14 hours with backlight ON (alkaline cells)
- ⊳ Weight : 31 ounces (885 g)
- Size: 6.7"w x 2.8"h x 4.1"d (170mm x 71mm x 103mm)

## ABS CARRYING CASE

> Weight (full): 16.4 lb. (7.43 Kg)

Size: 18.5"w x 14.6"h x 7.5"d (470mm x 371mm x 190mm)





